

Typ: WSERD-534.446



Art.-No.: G8000429

Features:

Luftstromwächter, elektronisch, Kanalmontage

Application:

Technical Data:

Dimensions of housing:	136mm x 85mm x 69mm
Number of outputs:	2
Output signal:	schaltend, 100-240V AC oder 24V \pm 10% AC/DC
Output signal:	schaltend, 100-240V AC oder 24V \pm 10% AC/DC
Switching off delay:	zwischen 2 und 20 Sekunden
Rated impulse voltage:	4000 V
Operating voltage:	100-240V AC oder 24V \pm 10% AC/DC
Electrical connection:	Schraubklemmen
Colour of housing:	Oberteil transparent, Unterteil anthrazit
Sensor:	kalorimetrischer Sensor
Sensor material:	Fühlergehäuse Aluminium mit Polyamid PA6
Material of housing:	Gehäusedeckel Polycarbonat, Gehäuseunterteil ABS, Kabelverschraubung PA6
max. switching voltage:	max. 250 V AC
max. switching current:	max. 8 A
Installation/fastening:	Kanalmontage
Surface quality:	matt
potential-free:	yes
Switching element:	Relais
Switching contact:	2 Wechsler
Degree of protection:	Gehäuse IP65, Fühler IP54

Protection class:	2
Ambient temperature:	Gehäuse 0 ... +50 °C / Fühler -20 ... +90°C
Degree of fouling:	2
Permissible atmospheric humidity:	