

Datasheet FTRFBU180.117/V2

Articlenumber: BA010200

Wireless room temperature sensor with timer, surface-mounted

Wireless room temperature sensor for recording and setting the room temperature with timer. Single-room temperature control is achieved if used in combination with alre wireless actuators. A sensor indicates a battery change is needed imminently.



Actual temperature display	Yes
Adaptive heating time start	Yes
Ambient temperature, lower value	-10 °C
Ambient temperature, upper value	50 °C
Assembly	Complete device
Bearing temperature, lower value	-10 °C
Bearing temperature, upper value	50 °C
Colour	Pure white
Control range, lower value	5 °C
Control range, upper value	30 °C
Cooling control function	Yes
Design	Berlin 3000
Display type	LCD, illuminated
ECO function (reduction)	Yes
External setting	Yes
Heating control function	Yes
Housing material	Plastic ABS
Internal setting	No

Manual setpoint adjustment	Yes
Material quality	Thermoplast
Maximum air humidity (non-condensing)	95 % r.H
Medium	Air, not aggressive
Mounting / attachment	Surface mounting
Operating voltage	2x micro AAA batteries, 1.5 V
Operation	Rotary knob and buttons
Protection class	III
Radio frequency	868 MHz
RAL colour number (similar)	9010
Range	150m line of sight/up to 30m in buildings
Safety and EMC	In accordance with DIN EN 60730
Sensor element	NTC internal
Surface properties	Matt
Surface protection	Untreated
Type of protection	IP30
Valve protection function	Yes
Wireless bidirectional	No
Wireless bus bus system	Yes
With bus connection	Yes
With display	Yes
With LED display	Yes
With on-site operation	Yes
With protection against theft/dismantling	No