

Datasheet SAUNATHERM VU

Articlenumber: D4700653

Sauna control for dry saunas, 30...120...°C, max. 9kW



"Display" "Heating", "On/Off", Preselection timer"	Yes
Ambient temperature, lower value	-15 °C
Ambient temperature, upper value	25 °C
Assembly	Control unit, sensor/STB, screws
Colour	Cream white
Control range, dry sauna lower value	30 °C
Control range, dry sauna upper value	120 °C
Depth	70 mm
Electric connection	Screw terminals
Fan On/Off switch	Yes
Fuse	T1, 25A (5x20)
Heating time limitation	6H/12h/none
Height	237 mm
Housing material	Plastic ABS
Maximum air humidity (non-condensing)	95 % r.H
Mounting / attachment	Wall mounting
Operating voltage	400 V AC, 3/N 50Hz
Preselection timer	Can be set to max. 12h / 1h steps
Protection class	II, following appropriate mounting

RAL colour number (similar)	9001
STB trigger temperature	141 °C
Switching difference	Approx. 1 K
Switching element	Safety guard, relay 3-stage switching
Switching power fan	100 W
Switching power light	100 W
Switching power oven	9 kW
Type of accessories/spare part	Sauna control
Type of protection	IP44
Water shortage detection	Yes
Width	212 mm
With LED display	Yes

