

Datasheet RTKSA-101.110

Articlenumber: KA010101

Control Room thermostat, 0...50...°C, hysteresis 1.3K, TW, internal setting



Ambient temperature, upper value	50 °C
Bearing temperature, lower value	-30 °C
Bearing temperature, upper value	80 °C
Colour	Anthr. grey (RAL7016), frontp. transp.
Control range, lower value	0 °C
Control range, upper value	50 °C
Cooling control function	Yes
Depth	57,5 mm
Device version	Surface-mounted unit
Electric connection	Push-in terminal
Electronic control	No
External setting	No
Function type (systems engineering)	TW
Heating control function	Yes
Height	146,8 mm
Internal setting	Yes
Max. sensor temperature	57 °C
Maximum air humidity (non-condensing)	95 % r.H
Maximum switching current	O: 16 (2,5) A; S: 6,3 (2,5) A, 0,25 ADC
Maximum switching voltage	230 V AC 50 / 60 Hz, 230 V DC

Medium	Air, not aggressive
Minimum switching current	At 24 V (AC/DC) min. 100 mA
Minimum switching voltage	24 V AC / 50 Hz, 24 V DC
Mounting / attachment	Wall mounting
Number of control ranges	1
Number of outputs	2
Operating voltage	None
Operation	Internal setpoint adjuster
Output signal	Switching
Potential free switching contact	Yes
Protection class	I
Safety and EMC	In accordance with DIN EN 60730
Scale	Degree Celsius
Sensor element	Capillary tube
Sensor material	V2A
Switching contact	Two-way contact
Switching difference	1.3 K
Switching difference, can be adjusted	No
Switching element	Microswitch
Type of protection	IP54
Width	85 mm
With explosion protection	No

