


Datasheet FHY 101.060#00

Articlenumber: UA020004

Room hygostat, surface-mounted, 24V AC to 230V AC, 35...85% r.H., two-way contact

The room hygostat is designed for monitoring and controlling relative humidity, e.g. in business premises, apartments, conservatories, bathrooms, swimming pools, computer rooms and other spaces with a clean, non-aggressive environment. Relative humidity acting on a measuring strip activates a potential-free switch contact. The setpoint is adjusted using the adjustment knob located on the front. The setting range can be restricted. Can be adapted for use in nearly all rocker switch ranges with cover set 50 x 50 mm or 55 x 55 mm. Compatible cover set no. JZ-001.xxx.



Ambient temperature, lower value	0 °C
Ambient temperature, upper value	50 °C
Assembly	Complete device
Bearing temperature, lower value	-20 °C
Bearing temperature, upper value	60 °C
Can be read off	No
Colour	Top part as cover set, UT anthracite
Contact interlocking	No
Cooling control function	No
Degree of contamination	2
Depth	42,5 mm
Design	Berlin UP
Digital display	No
Display	No
Electric connection	Screw terminals
External setting	Yes

Heating control function	No
Height	71 mm
Housing material	Plastic PC
Humidify / dehumidify control function	Yes
Internal setting	No
Maximum air humidity (non-condensing)	95 % r.H
Maximum switching current	E: 5 (0,2) A ; B: 2 (0,2) A
Maximum switching voltage	230 V AC, 50 Hz
Mechanical range reduction	Yes
Medium	Air, not aggressive
Minimum switching current	100 mA
Minimum switching voltage	24 V AC / 50 Hz
Mounting / attachment	Flush mounting (deep socket recommended)
NEMA type of protection	Other
Number of outputs	2
On / Off switch	No
Operating voltage	None
Operation	Rotary knob
Output signal	Switching (230 V AC / 24 V AC, 50 Hz)
Potential free switching contact	No
Protection class	II, following appropriate mounting
Safety and EMC	In accordance with DIN EN 60730
Sealable	No
Sensor element	Plastic fibres
Setting range, rel. air humidity lower value	35 %
Setting range, rel. air humidity upper value	85 %
Surface properties	Matt or gloss (see cover set)
Switching contact	Two-way contact
Switching difference	Approx. 5% r.H.
Switching difference, can be adjusted	No
Switching element	Microswitch
Switching power	1150 W bzw. 460 W

Type of protection	IP30
Width	71 mm
With explosion protection	No
With thermostat	No