

Datasheet KTRVB-052.244

Articlenumber: DA451500

Room thermostat, heating/cooling, surface-mounted, 24VAC/VDC, output 0...10V/10...0V, 2-/4-tube

Electronic surface-mounted air conditioning controller for heating/cooling control in 2- and 4-pipe systems for hotel, residential and commercial premises. Designed to control continuous valve actuators, both normally closed and normally open. Particularly suitable for cooling ceiling control due to the possibility of dew point monitoring. To compensate for the inertia of controlled systems with cooling ceilings, the device has a temperature sensor input for connecting an external radiation sensor (optional). The factory-set "zero point" of approx. 21 °C can be adjusted by ± 5 K in the device. The setpoint temperature can be adjusted by ± 3 K around the set zero point using the adjustment knob. The external sensor can also be designed as a room sensor (optional) as an official variant, where the controller should be inaccessible to unauthorized persons. An internal potentiometer can be used to select the use of the internal or external sensor or the use of both sensors with an adjustable weighting. Contact inputs for ECO function and OFF (frost protection).



Actual temperature display	No
Additional heating switch	No
Ambient temperature	0 ... 40 °C
Assembly	Complete device
Bearing temperature	-20 ... 70 °C
Colour	Pure white
Control behaviour	PI
Control range	13 ... 29 °C
Cooling control function	Yes
Degree of contamination	2
Design	Berlin 2000
Dimensions (W x H x D)	78,3 mm x 83,4 mm x 25,5 mm
Display	No

ECO function (reduction)	Yes
ECO input (reduction)	24 VAC, 50 Hz / 24 VDC
Electric connection	Screw terminals
Electronic control	Yes
External setting	Yes
Heating control function	Yes
Housing material	Plastic ABS
Max. air humidity (non-condensing)	95 % r.H.
Max. switching current	5 mA
Mechanical range reduction	Yes
Medium	Air
Montage/Befestigung	Surface mounting
Neutral zone	2 K
Number of outputs	2
Number of outputs, cooling	1
Number of outputs, heating	1
Operating voltage	24 VAC, 50 Hz / 24 VDC
Operation	Rotary knob
Output signal	Continuous, 0 ... 10 V
Potential free switching contact	No
Protection class	III
RAL colour number (similar)	9010
Safety and EMC	In accordance with DIN EN 60730
Scale	Threshold arrows with "+" and "-"
Schalter Aus/Komfort/ECO	No
Schalter Ein/Aus	No
Schalter Heizen/Kühlen	No
Sensor element	NTC internal, optional NTC external
Sensor external	No
Surface finish	Matt
Switch/lamp night-time reduction	No
Switching contact	Zero-contact

Switching difference, can be adjusted	No
Switching differential	Heating/cooling: 0 K
Switching element	Electronics with analogue output signal
Temperature controller version	Climate controller
Type of wiring	Other
With receiver	No

