

Datasheet KTRVB-052.245

Articlenumber: DA451600

Room thermostat, heating/cooling, surface-mounted, 24VAC/VDC, output 0...10V/10...0V, 2-/4-pipe, switch Off/Comfort/ECO

Electronic surface-mounted air conditioning controller for heating/cooling control in 2- and 4-pipe systems for hotel, residential and commercial premises. Designed to control continuous valve actuators, both normally closed and normally open. The switch can be used to select between the operating modes Off/Comfort/ECO. The dew point monitoring option makes it particularly suitable for cooling ceiling control. To compensate for the inertia of controlled systems with cooling ceilings, the device has a temperature sensor input for connecting an external radiation sensor (optional). The factory-set "zero point" of approx. 21 °C can be adjusted by ± 5 K in the device. The setpoint temperature can be adjusted by ± 3 K around the set zero point using the adjustment knob. The external sensor can also be designed as a room sensor (optional) as an official variant, where the controller should be inaccessible to unauthorized persons. An internal potentiometer can be used to select the use of the internal or external sensor or the use of both sensors with an adjustable weighting. Contact inputs for ECO function and OFF (frost protection).



Actual temperature display	No
Additional heating switch	No
Ambient temperature	0 ... 40 °C
Assembly	Complete device
Bearing temperature	-20 ... 70 °C
Colour	Pure white
Control behaviour	PI
Control range	13 ... 29 °C
Cooling control function	Yes
Degree of contamination	2
Design	Berlin 2000
Dimensions (W x H x D)	78,3 mm x 83,4 mm x 25,5 mm
Display	No

ECO function (reduction)	Yes
ECO input (reduction)	24 VAC, 50 Hz / 24 VDC
Electric connection	Screw terminals
Electronic control	Yes
External setting	Yes
Heating control function	Yes
Housing material	Plastic ABS
Max. air humidity (non-condensing)	95 % r.H.
Max. switching current	5 mA
Mechanical range reduction	Yes
Medium	Air
Montage/Befestigung	Surface mounting
Neutral zone	2 K
Number of outputs	2
Number of outputs, cooling	1
Number of outputs, heating	1
Operating voltage	24 VAC, 50 Hz / 24 VDC
Operation	Rotary knob and switches
Output signal	Continuous, 0 ... 10 V
Potential free switching contact	No
Protection class	III
RAL colour number (similar)	9010
Safety and EMC	In accordance with DIN EN 60730
Scale	Threshold arrows with "+" and "-"
Schalter Aus/Komfort/ECO	Yes
Schalter Ein/Aus	No
Schalter Heizen/Kühlen	No
Sensor element	NTC internal, optional NTC external
Sensor external	No
Surface finish	Matt
Switch/lamp night-time reduction	No

Switching contact	Zero-contact
Switching difference, can be adjusted	No
Switching differential	Heating/cooling: 0 K
Switching element	Electronics with analogue output signal
Temperature controller version	Climate controller
Type of wiring	Other
With receiver	No

