

Datasheet ZBOOA-010.100

Articlenumber: H9100010

Heating valve actuator, 230VAC, normally closed

Electrothermal valve actuators for heating, ventilation and air conditioning systems. The actuator is very space-saving thanks to its compact design. The tapered design, especially in the mounting area of the nut, makes installation easy to handle. The fixing cable is not located in the area of the fixing nut. This reduces the likelihood of contact with devices carrying hot water. As the fixing nut allows the valve to be screwed onto the thread continuously, it is possible to open the valve in a de-energized state by turning the nut back by two to three thread turns, unlike bayonet and snap-on couplings. Leaking water is drained away via a drainage system. A special design eliminates the need for seals. The current valve position is displayed at 2 positions (top and side). Due to their M 30 x 1.5 mounting and their characteristics (normally closed), the valve actuators are suitable for the following valve and distributor brands: Beulco, Empur, Heimeier, Kamo, Oventrop, Purmo, SBK, SKV, Strawa, Taconova, Watts.



Ambient temperature	0 ... 50 °C
Average power consumption	3 W
Bearing temperature	-20 ... 70 °C
Cable length	0.8 m
Colour	Pure white
Connection cross-section	2 x 0,5 ()
Control signal	2-point
Dimensions (W x H x D)	39 mm x 39 mm x 57 mm
Function type	Closed when de-energised
Housing material	Plastic PC
Max. air humidity (non-condensing)	95 % r.H.
Max. Inrush current	Ca. 0,3 A
Max. power consumption	70 W
Montage/Befestigung	M30x1.5

Nominal closing force	90 N
Nominal stroke	3 mm
Operating voltage	230 VAC, 50 Hz
Protection class	II, following appropriate mounting
RAL colour number (similar)	9010
Running time	240 s
Safety and EMC	In accordance with DIN EN 60730
Temperature controller version	Valve actuator
Valve setting display	Double (top and side)