

Datasheet RTBSB-001.065

Articlenumber: MA010600

Room thermostat, surface-mounted, 5...30°C, 230VAC, changeover contact, heating/cooling switch

Electromechanical room thermostat in a surface-mounted housing for controlling or monitoring temperatures in offices, living rooms and hotels. Especially for 2-pipe air conditioning systems. The heating/cooling changeover takes place with the heating/cooling switch. A very precise switching differential is achieved through thermal feedback. The setting range can be changed using the range restriction located under the setting knob.



Ambient temperature	0 ... 30 °C
Assembly	Complete device
Bearing temperature	-20 ... 70 °C
Colour	Pure white
Connection cross-section	0,12 – 2,5 mm ²
Control behaviour	2-point
Control range	5 ... 30 °C
Cooling control function	Yes
Design	Berlin 2000
Dimensions (W x H x D)	78,3 mm x 83,4 mm x 25,5 mm
ECO function (reduction)	No
Electric connection	Screw terminals
Energy efficiency class	I
External setting	Yes
Heating control function	Yes
Heating display	No
Housing material	Plastic ABS

Internal setting	No
Max. air humidity (non-condensing)	95 % r.H.
Max. power consumption	< 0,5 W
Max. switching current	5 (2) A
Max. switching voltage	230 VAC, 50 Hz
Mechanical range reduction	Yes
Medium	Air
Min. switching voltage	230 VAC, 50 Hz
Montage/Befestigung	Surface mounting
Number of control ranges	1
Number of outputs	1
Number of outputs, cooling	1
Number of outputs, heating	1
Operating voltage	230 VAC, 50 Hz
Operation	Rotary knob and switches
Output signal	Switching
Potential free switching contact	No
Protection class	II, following appropriate mounting
RAL colour number (similar)	9010
Safety and EMC	In accordance with DIN EN 60730
Scale	Degree Celsius
Schalter Ein/Aus	No
Schalter Heizen/Kühlen	Yes
Sensor element	Bimetal
Surface finish	Matt
Switching contact	Two-way contact
Switching differential	Heating/cooling: 0,5 K (delta T max. 4 K/h)
Switching element	Bimetal contact
Switching power	1150 W
Test mark approval	CE
Thermal feedback	Yes

